



TranSpec®

Process Spectrometer with Integrated Spectral Lamp

TranSpec instruments are photodiode array spectrometers, which combine most innovative optoelectronics with powerful analog/digital electronics. With the use of flexible optical fibers, TranSpec's application area ranges from standard lab analysis to specialized in-line process measurement tasks.



Innovative Optical Components

The TranSpec instruments exclusively use spectrometer modules of Carl Zeiss, Germany. With these modules, the entrance slit is imaged on a photodiode array by means of a holographic created, concave diffraction grating. All components of the spectrometer module are firmly mounted together in one unit and permanently adjusted to each other, which means that there are no mechanically moveable parts at all.

Powerful Analog/Digital Electronics

For the scanning of the photodiode array and the A/D-conversion of measured spectra, TranSpec spectrometers use a fast and highly linear 1 MHz A/D-converter. Due to the extremely short scanning time of the photodiode array (approx. 256 microseconds for an array of 256 photodiodes) the TranSpec instruments can be described as real simultaneous spectrometers. The high linearity of the A/D-converter permits reliable, reproducible photometric measurements over the entire useable signal dynamic range. The TranSpec spectrometers use the industry standard USB 2.0 interface to connect to your PC.

Integrated High-Power Spectral Lamp

The TranSpec process spectrometers are assembled with either a high-power halogen or with a special combined deuterium/halogen spectral lamp in shine-through technology. The spectral lamps provide an integrated automatic shutter, bulb burn control, running time meters and fiber optics connection.

Technical specifications on next page ►



TranSpec Process Spectrometer • Technical Specifications

May 2011, all information without guarantee and subject to changes

Mechanical Construction

- Standard 19" chassis with 3 HU, CE certificate
- Dimensions: approximately 132 x 435 x 370 mm (H x W x D)
- Weight: approximately 9 kg

Optical Components

- Spectrometer modules of Carl Zeiss Germany with industry standard FSMA fiber optics connector
- Holographic created concave diffraction grating
- Photodiode arrays with 256, 512 or 1024 pixel, no cooling required
- Permanently adjusted modules, no mechanically moveable parts, free of maintenance
- Module specific wavelength ranges: 200 - 1100 nm
- Module specific spectral resolution: 3 - 10 nm
- Module specific spectral pixel interval: approx. 0.8 - 3.3 nm
- Absolute wavelength accuracy: ≤ 0.3 nm
- Temperature drift: typically < 0.005 nm / Kelvin

Analog/Digital Electronics

- 1 MHz 16 bits AD-converter AD7677 from Analog Devices, Inc.
- Spurious-free dynamic range, no missing codes at 16 bits
- Effectively useable conversion rate: 1 microsecond per pixel
- TTL shutter and bulb burning control for integrated spectral lamp
- Optional external USB multi-i/o module with 8 x TTL and 4 x analog output
- Standard USB 2.0/3.0 interface to connect laptop or PC
- Optional Ethernet (LAN) interface to connect laptop or PC

Integrated Halogen Lamp or Deuterium/Halogen Lamp

- 20 watt or 50 watt high-power halogen lamp
- Optional combined deuterium/halogen lamp (35/7 watt) as shine-through, separate use of each bulb possible
- Software controlled bulb on/off status
- Integrated mechanical shutter, software controlled
- Integrated running time meters, one each for halogen and deuterium bulb

Spectra Scanning

- Shortest integration time: 0.4 ms at 256 pixel – 0.7 ms at 512 pixel – 1.2 ms at 1024 pixel
- Longest integration time: up to 5 seconds for all modules, selectable in steps of 0.1 ms
- Raw data averaging, selectable between 2-100
- Total system noise (standard deviation, dark current at 10 ms): 5 Counts/no averaging, 2 Counts/25 measurements
- Date and time stamping of each, unique measured spectrum with a resolution of 1 microsecond

Available Software

- FTM-ProVis Professional software for in-line film thickness measurement in process environment
- FTM-Lite++ comfortable C/C++ class libraries for developing your own applications
- Development of customized software, especially for in-line process controlling tasks

Note TranSpec is a registered German trademark of Dipl.-Ing. (FH) Th. Fuchs, Engineer's Office for Applied Spectroscopy. All other mentioned product names are or possibly might be trademarks or registered trademarks of their owners.